



ALTEX NATURETONE

EXTERIOR & INTERIOR EMULSION PAINT

- DESCRIPTION** : ALTEX NATURETONE is a premium quality, modified acrylic emulsion paint that endures and washable. Recommended for exterior as well as interior use with anti fungus, algae and mold properties.
- TYPE** : Acrylic modified emulsion
- GLOSS** : Mat finish
- THEORITICAL COVERAGE** : $\pm 3 - 4 \text{ m}^2/\text{kg}$
- VISCOSITY (poise), 30° C** : 15 ± 1
- SPECIFIC GRAVITY, 30° C** : 1.46 ± 0.07
- DRYING TIME** : 1 – 2 hours
- THINNER** : Clean water, approx. 20 - 30 %
- METHOD OF APPLICATION** : Brush, roller or spray
- PRETREATMENT** : Cleaning
- New Surfaces must be cleaned from loose dirt and dust etc.
 - ◆ Minor cracks, holes, leakage and loose plaster must be repaired.
 - ◆ The new surfaces need minimal 21 days for normal drying.
 - ◆ Moisture < 6 %, Alkali 6 - 10
 - ◆ Then apply 1 coat of ALTEX NATURETONE PRIMER
 - ◆ Wall filler is suggested only for minor cracks.
 - ◆ Then apply 2 – 3 coats of ALTEX NATURETONE.
 - Previously painted surfaces must be cleaned from dirt, dust, fungus algae and flaking old paint.
 - ◆ Moisture < 6 %, Alkali 6 - 10
 - ◆ Then apply 1 coat of ALTEX NATURETONE PRIMER
 - ◆ Wall filler is suggested only for minor cracks.
 - ◆ Then apply 2 – 3 coats of ALTEX NATURETONE.
- ATTENTION** : The work should be carried out on dry surfaces.

Issued 060712

This data sheet supercedes those previously issued